



## Walker LED 6,5W 3000K

Design: Studio Tecnico Ivela



IP 67 IK 10



Product Code	Color
1553181	Stainless steel

## General specifications

Product type	Outdoor recessed
Mounting type	Ground - recessed
Mounting location	Ground
Indoor/Outdoor light	Outdoor
Description	Recessed uplight fitting, suitable for vehicles flush with the ground with supply voltage LED dimmable on the mains. It is ideal to highlight paths and can be absolutely integrated in the ambient and easy to install. Screen in opal polycarbonate, unbreakable, unalterable. With supply voltage LED dimmable on the mains. Protection rating IP67. Recessed housing included in the fittings.
Applications	Walkways , Vehicles and pedestrian traffic , Natural features , Green areas

## Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 850lm 6,5W 3000K CRI80
Nominal lumens on thermal regime (lm)	850
Delivered lumen (lm)	367
Watt source (W)	6.5
Color temperature (K)	3000
CRI	CRI 80
Lamp type	COB LED
Photobiological risk group	RG1

## Physical specifications

Body	Inner and recessed housing in high resistant technopolymer
Mechanical load (kg)	2000
Screws	Stainless steel

## Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	230/240
Frequency (Hz)	50/60
Cable gland	PG11 in polyamide

## Optical specifications

Light distribution	Symmetric
Emission	Direct
Light beam	100°

## Weight and dimension

Diameter (mm)	175
Recessed depth (mm)	270
Temperature max (°C)	60
Weight (Kg)	1.2

Accessories



Product Code 160821  
Name 10mt Supply cable coil, H05RN-F 2x1 mm²



Product Code 84108  
Name IP 68 rated cable connector  
IP rating IP 68