
### 48VDC TL Recessed track


# 2mt

Design: Ivela Design Team



644
Ge
Pro
Мо











IP 20

































#### **Product Code** Color

46-20-30

# neral specifications

oduct type Tracks

Ceiling - recessed ounting type

Indoor/Outdoor light Indoor

Description 48V low voltage electrified track for trimless recessed installation in false ceilings., compatible with spotlights equipped with the specific 48V adapter. The two conductors can transmit also the DALI signal, allowing for the dynamic control of the single light

sources. The continuity of the positive line between each element is important for a correct installation of all the accessories.

Maximum load: 720W

Black

# Physical specifications

Finishing Extruded aluminium alloy, polyester painted. Load capacity description The track has a load capacity of 4 Kg every 1000 mm. For a 4 Kg load every 200 mm, a maximum fixing distance of 500 mm is recommended.

# **Electrical specifications**

48 Voltage (V) Current (A) 15

### Weight and dimension

2000 Length (mm) Height (mm) 23 Width (mm)

#### Accessories

6480-10-30 Product Code Right live-end Name

Packaging quantity 10 Finishing Black

Product Code 6480-11-30 Left live-end Name

10 Packaging quantity Finishing Black

Product Code 6481-00-30 Central connector Name

Packaging quantity 5 Finishing Black

Product Code 6453-00-30 Name Straight connector

Packaging quantity 25 Finishing Black Product Code 6454-10-30

Name Mechanical joint without electrical contacts

Packaging quantity 25 Finishing Black



