


Microperfetto-R 21W 3000K

Design:



IP 20



Product Code	Color
757-479BN-16	Black

General specifications

Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Spotlight with prismatic spread lens and canopy for recessed application, specially developed for high efficiency COB LEDs. Professional optics for different beam angles and optical devices for better visual comfort are available. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver.

Applications	Retail , Residential , Hospitality
--------------	------------------------------------

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 2350lm 21W 3000K CRI90
Nominal lumens on thermal regime (lm)	2350
LOR	70
Delivered lumen (lm)	1645
Watt source (W)	21
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 330° about vertical axis and pivot up to 90° upwards.
Light beam	30°

Weight and dimension

Length (mm)	95
Height (mm)	116
Width (mm)	53
Cutout diameter (mm)	55
Recessed depth (mm)	50
Weight (Kg)	0.4

Accessories

Product Code	28-9001-51
Name	Professional optic device S
Light beam	16°
Finishing	Mirror metallized



Product Code	28-9002-51
Name	Professional optic device M
Light beam	30°
Finishing	Mirror metallized



Product Code	28-9003-51
Name	Professional optic device W
Light beam	45°
Finishing	Mirror metallized



Product Code	28-4139-100
Name	Satined gold baffle



Product Code	28-4139-31
Name	White baffle



Product Code	28-4163-30
Name	Honeycomb
Finishing	Black painted



Product Code	28-4073-103
Name	Elliptical spread lens

Driver

Product Code	81-04022
Name	Driver 600mA
Driver current (mA)	600