


## Nanoperfetto Base 6W 2700K CRI90 21°

Design: Ivela Design Team



IP 40



| Product Code   | Color     |
|----------------|-----------|
| 752-729CYN0-21 | Mat white |

### General specifications

|                      |   |
|----------------------|---|
| Product type         | Semi- recessed surface spotlights   |
| Indoor/Outdoor light | Indoor  |
| Description          | Spotlight with PMMA lenses for surface installation, specially developed for high efficiency COB LED. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver. |
| Applications         | Shops , Showrooms , Residential   |

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

|                                       |                          |
|---------------------------------------|--------------------------|
| Lamp description                      | LED 579lm 6W 2700K CRI90 |
| Nominal lumens on thermal regime (lm) | 579                      |
| LOR                                   | 86                       |
| Delivered lumen (lm)                  | 498                      |
| Watt source (W)                       | 6                        |
| Color temperature (K)                 | 2700                     |
| CRI                                   | CRI 90                   |
| Lamp type                             | COB LED                  |
| Average lamp life (h)                 | L80B10 50.000            |
| Photobiological risk group            | RG1                      |
| Unified Glare Rating (U.G.R. <)       | 5                        |

### Physical specifications

|                     |                    |
|---------------------|--------------------|
| Body                | Die-cast aluminium |
| Finishing           | Polyester painted  |
| Optic device        | PMMA lens          |
| Thermal dissipation | Passive            |

### Electrical specifications

|                     |                                       |
|---------------------|---------------------------------------|
| Driver availability | Separate                              |
| Driver mounting     | Separate                              |
| Dimmable            | Dimmable on the mains / DALI dimmable |
| Frequency (Hz)      | 50/60                                 |

### Optical specifications

|                    |           |
|--------------------|-----------|
| Light distribution | Symmetric |
| Emission           | Direct    |
| Aiming             | Fixed     |
| Light beam         | 21°       |

### Weight and dimension

|               |     |
|---------------|-----|
| Length (mm)   | 57  |
| Diameter (mm) | 36  |
| Weight (Kg)   | 0.1 |

**Accessories**

---



Product Code 28-4499-30  
Name Honeycomb



Product Code 81-04026  
Name Driver 500mA DALI  
Description For a correct installation, consider a ceiling recessed depth of 200mm



Product Code 81-04029  
Name Driver 500mA dimmable on the mains



Product Code 81-04087  
Name Driver 500mA Wireless Bluetooth