


Nanoperfetto Base 6W

3000K CRI90 38°

Design: Ivela Design Team



IP 40



| Product Code | Color |
|----------------|-----------|
| 752-729BWN0-21 | Mat white |

General specifications

| | |
|----------------------|---|
| Product type | Semi- recessed surface spotlights |
| Indoor/Outdoor light | Indoor |
| Description | Spotlight with PMMA lenses for surface installation, specially developed for high efficiency COB LED. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver. |
| Applications | Shops , Showrooms , Residential |

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

| | |
|---------------------------------------|--------------------------|
| Lamp description | LED 611lm 6W 3000K CRI90 |
| Nominal lumens on thermal regime (lm) | 611 |
| LOR | 86 |
| Delivered lumen (lm) | 525 |
| Watt source (W) | 6 |
| Color temperature (K) | 3000 |
| CRI | CRI 90 |
| Lamp type | COB LED |
| Average lamp life (h) | L80B10 50.000 |
| Photobiological risk group | RG1 |
| Unified Glare Rating (U.G.R. <) | 12 |

Physical specifications

| | |
|---------------------|--------------------|
| Body | Die-cast aluminium |
| Finishing | Polyester painted |
| Optic device | PMMA lens |
| Thermal dissipation | Passive |

Electrical specifications

| | |
|---------------------|---------------------------------------|
| Driver availability | Separate |
| Driver mounting | Separate |
| Dimmable | Dimmable on the mains / DALI dimmable |
| Frequency (Hz) | 50/60 |

Optical specifications

| | |
|--------------------|-----------|
| Light distribution | Symmetric |
| Emission | Direct |
| Aiming | Fixed |
| Light beam | 38° |

Weight and dimension

| | |
|---------------|-----|
| Length (mm) | 57 |
| Diameter (mm) | 36 |
| Weight (Kg) | 0.1 |

Accessories



Product Code 28-4499-30
Name Honeycomb



Product Code 81-04029
Name Driver 500mA dimmable on the mains



Product Code 81-04026
Name Driver 500mA DALI
Description For a correct installation, consider a ceiling recessed depth of 200mm



Product Code 81-04087
Name Driver 500mA Wireless Bluetooth