


## Nanoperfetto Base 6W

### 3000K CRI90 38°

Design: Ivela Design Team



IP 40



Product Code	Color
752-729BWN0-16	Black

#### General specifications

Product type	Semi- recessed surface spotlights
Indoor/Outdoor light	Indoor
Description	Spotlight with PMMA lenses for surface installation, specially developed for high efficiency COB LED. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver.
Applications	Shops , Showrooms , Residential

#### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 611lm 6W 3000K CRI90
Nominal lumens on thermal regime (lm)	611
LOR	86
Delivered lumen (lm)	525
Watt source (W)	6
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	12

#### Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	PMMA lens
Thermal dissipation	Passive

#### Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable
Frequency (Hz)	50/60

#### Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	38°

#### Weight and dimension

Length (mm)	57
Diameter (mm)	36
Weight (Kg)	0.1

**Accessories**

---



Product Code 28-4499-30  
Name Honeycomb



Product Code 81-04029  
Name Driver 500mA dimmable on the mains



Product Code 81-04026  
Name Driver 500mA DALI  
Description For a correct installation, consider a ceiling recessed depth of 200mm



Product Code 81-04087  
Name Driver 500mA Wireless Bluetooth