


**Perfetto-IN 40 with lens**  
**2700K CRI90 14°**

Design:



IP 43 IK 07



Product Code	Color
254-219CZN-16	Black

**General specifications**

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight with no replaceable lens and prismatic spread lens, equipped with LED of latest generation. Inner snoot in black thermoplastic material. LED drivers should be ordered separately for installation through the recessed hole; the wattage of the fitting changes depending on the selected driver.
Applications	Commercial areas , Showrooms , Residential , Hospitality

**Lighting specifications****i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 180lm 3W 2700K CRI90
Nominal lumens on thermal regime (lm)	180
LOR	85
Delivered lumen (lm)	153
Watt source (W)	3
Color temperature (K)	2700
CRI	CRI 90
Lamp type	High Power LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	9

**Physical specifications**

Body	Die-cast aluminium
Finishing	Polyester painted
Thermal dissipation	Passive

**Electrical specifications**

Driver availability	Separate
Driver mounting	Separate

**Optical specifications**

Light distribution	Symmetric
Emission	Accent light
Aiming	Fixed
Light beam	14° Lens

**Weight and dimension**

Height (mm)	45
Diameter (mm)	41
Cutout diameter (mm)	36
Recessed depth (mm)	45
Weight (Kg)	0.1
False ceiling thickness (mm)	1-30

**Accessories**

---



Product Code	28-4105-100
Name	Satined gold baffle



Product Code	81-02531
Name	Driver 700mA Constant current
Description	Max 3 fittings