


**Perfetto-IN 50 with lens 6W
2700K CRI90 38°**

Design:



IP 43 IK 08



Product Code	Color
225-039CWN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight with PMMA lens and frosted thermoplastic screen, equipped with COB LED of latest generation. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fitting changes depending on the selected driver.
Applications	Shops , Showrooms , Residential , Hospitality

Lighting specifications**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 579lm 6W 2700K CRI90
Nominal lumens on thermal regime (lm)	579
LOR	86
Delivered lumen (lm)	498
Watt source (W)	6
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	PMMA lens
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Light beam	38° Lens

Weight and dimension

Height (mm)	50
Diameter (mm)	50
Cutout diameter (mm)	43
Recessed depth (mm)	50
Weight (Kg)	0.1
False ceiling thickness (mm)	1-20

Accessories



Product Code 28-4499-30
Name Honeycomb



Product Code 81-04026
Name Driver 500mA DALI
Description For a correct installation, consider a ceiling recessed depth of 200mm



Product Code 81-04029
Name Driver 500mA dimmable on the mains



Product Code 81-04087
Name Driver 500mA Wireless Bluetooth