



Perfetto-IN 70 12W 3000K
CRI90 21°

Design:



IP 43 IK 08



Product Code	Color
262-039BNY-21	Mat white

General specifications

Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver.
Applications	Commercial areas , Showrooms , Residential , Hospitality

Lighting specifications

Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1470lm 12W 3000K CRI90
Nominal lumens on thermal regime (lm)	1470
LOR	58
Delivered lumen (lm)	853
Watt source (W)	12
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	3
Closing screen	Clear thermoplastic material

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	21°

Weight and dimension

Height (mm)	83
Diameter (mm)	70
Cutout diameter (mm)	64
Recessed depth (mm)	83
Weight (Kg)	0.3
False ceiling thickness (mm)	1-30

Accessories

Product Code 28-4039-100
Name Satined gold baffle



Product Code 28-4039-31
Name White baffle



Product Code 28-4208-30
Name Honeycomb
Finishing Black painted



Product Code 28-4065-47
Name Prismatic spread lens , to be used only instead of included closing screen



Product Code 28-4065-61
Name Frosted glass, to be used only instead of included closing screen



Product Code 28-4065-103
Name Elliptical spread lens, to be used only instead of included closing screen



Product Code 81-04003
Name Driver 350mA DALI dimmable



Product Code 81-04010
Name Driver 350mA dimmable on the mains
Description Max 1 fitting