IVEL ^.

Perfetto-IN 70 12W 3000K CRI90 44°





IP 43 IK 08



Product Code	Color
262-039BNW-21	Mat white
General specifications	
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver.
Applications	Commercial areas , Showrooms , Residential , Hospitality
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle versio
Lamp description	LED 1470lm 12W 3000K CRI90
Nominal lumens on thermal regime (Im)	1470
LOR	58
Delivered lumen (Im)	853
Watt source (W)	12
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	3
Closing screen	Clear thermoplastic material
Physical specifications	
Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive
Electrical specifications	
Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable
Optical specifications	
Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	44°
Weight and dimension	
Height (mm)	83
Diameter (mm)	70
	64
Cutout diameter (mm)	U 1
Cutout diameter (mm)	83
Cutout diameter (mm) Recessed depth (mm) Weight (Kg)	83 0.3

IVEL ^.

Accessories







-

K.

Product Code Name

Product Code Name

Product Code Name Finishing

Product Code Name

Product Code Name

Product Code Name

Product Code Name

Product Code Name Description 28-4039-100 Satined gold baffle 28-4039-31 White baffle 28-4208-30 Honeycomb Black painted 28-4065-47 Prismatic spread lens , to be used only instead of included closing screen 28-4065-61 Frosted glass, to be used only instead of included closing screen 28-4065-103 Elliptical spread lens, to be used only instead of included closing screen

81-04003 Driver 350mA DALI dimmable

81-04010 Driver 350mA dimmable on the mains Max 1 fitting