


Perfetto-IN 70 12W 2700K CRI 90 21°

Design:















IP 43 IK 08



Product Code	Co	olor

General specifications

262-039CNY-21

Product type Downlights

Mounting type Ceiling - recessed

Indoor/Outdoor light Indoor

Description

Fixed downlight designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver.

Applications Commercial areas , Showrooms , Residential , Hospitality

L80B10 50 000

Mat white

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description LED 1430lm 12W 2700K CRI90

Nominal lumens on thermal regime (lm) 1430

 LOR
 58

 Delivered lumen (lm)
 830

 Watt source (W)
 12

 Color temperature (K)
 2700

 CRI
 CRI 90

 Lamp type
 COB LED

Photobiological risk group RG1
Unified Glare Rating (U.G.R. <) 3

Closing screen Clear thermoplastic material

Physical specifications

Average lamp life (h)

Body Die-cast aluminium
Finishing Polyester painted

Optic device Mirror-metallized thermoplastic material

Thermal dissipation Passive

Electrical specifications

Driver availability Separate
Driver mounting Separate

Dimmable on the mains / DALI dimmable

Optical specifications

Light distributionSymmetricEmissionDirectAimingFixedLight beam21°

Weight and dimension

Via B. Buozzi, 15

 Height (mm)
 83

 Diameter (mm)
 70

 Cutout diameter (mm)
 64

 Recessed depth (mm)
 83

 Weight (Kg)
 0.3

 False ceiling thickness (mm)
 1-30



Accessories



28-4039-100 Product Code Name Satined gold baffle



Product Code 28-4039-31 Name White baffle



28-4208-30 Product Code Name Honeycomb Finishing Black painted



28-4065-47 Product Code Name Prismatic spread lens, to be used only instead of included closing screen



28-4065-61 Product Code



Frosted glass, to be used only instead of included closing screen



Product Code 28-4065-103

Name

Elliptical spread lens, to be used only instead of included closing screen



Product Code 81-04003

Name

Driver 350mA DALI dimmable



Product Code 81-04010

Name Description Driver 350mA dimmable on the mains

Name

Max 1 fitting



Product Code 81-04090

Driver 350mA Wireless Bluetooth