
## Perfetto-IN 70 12W 2700K

## CRI 90 44°

Design:















IP 43 IK 08



Product Code	Color

262-039CNW-21 Mat white

General specifications

Product type Downlights

Mounting type Ceiling - recessed

Indoor/Outdoor light Indoor

Description Fixed downlight designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered

separately, the wattage of the fittings changes depending on the selected driver.

Applications Commercial areas , Showrooms , Residential , Hospitality

1430

Lighting specifications

Nominal lumens on thermal regime (Im)

Lamp description

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

LED 1430lm 12W 2700K CRI90

 LOR
 58

 Delivered lumen (Im)
 830

 Watt source (W)
 12

 Color temperature (K)
 2700

 CRI
 CRI 90

 Lamp type
 COB LED

 Average lamp life (h)
 L80B10 50.000

Photobiological risk group RG1
Unified Glare Rating (U.G.R. <) 3

Closing screen Clear thermoplastic material

**Physical specifications** 

Body Die-cast aluminium
Finishing Polyester painted

Optic device Mirror-metallized thermoplastic material

Thermal dissipation Passive

**Electrical specifications** 

Driver availability Separate
Driver mounting Separate

Dimmable Dimmable on the mains / DALI dimmable

**Optical specifications** 

Light distributionSymmetricEmissionDirectAimingFixedLight beam44°

Weight and dimension

Via B. Buozzi, 15 20050 Liscate • Milano

 Height (mm)
 83

 Diameter (mm)
 70

 Cutout diameter (mm)
 64

 Recessed depth (mm)
 83

 Weight (Kg)
 0.3

 False ceiling thickness (mm)
 1-30

T +39 02 9500121 • F +39 02 95001205



## Accessories



Product Code 28-4039-100

Name Satined gold baffle



Product Code 28-4039-31
Name White baffle



Product Code 28-4208-30
Name Honeycomb
Finishing Black painted



Name Prismatic spread lens , to be used only instead of included closing screen

28-4065-47



Product Code 28-4065-61



Product Code

Frosted glass, to be used only instead of included closing screen



Product Code 28-4065-103

Name

Elliptical spread lens, to be used only instead of included closing screen



81-04003

Name

Driver 350mA DALI dimmable



Product Code 81-04010

Name Driver 350mA dimmable on the mains

Description

Max 1 fitting

Product Code

81-04090

Name Driver 350mA Wireless Bluetooth