


**Perfetto-IN 70 2700K 12W**  
**CRI 90 44°**

Design:

**IP 43**   **IK 08**

Product Code	Color
262-039CNW-16	Black

**General specifications**

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight designed for COB LEDs, featuring a rearward optic for a high visual comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver.
Applications	Commercial areas , Showrooms , Residential , Hospitality

**Lighting specifications****i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1430lm 12W 2700K CRI90
Nominal lumens on thermal regime (lm)	1430
LOR	58
Delivered lumen (lm)	830
Watt source (W)	12
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	3
Closing screen	Clear thermoplastic material

**Physical specifications**

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

**Electrical specifications**

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable

**Optical specifications**

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	44°

**Weight and dimension**

Height (mm)	83
Diameter (mm)	70
Cutout diameter (mm)	64
Recessed depth (mm)	83
Weight (Kg)	0.3
False ceiling thickness (mm)	1-30

**Accessories**

Product Code 28-4039-100  
Name Satined gold baffle



Product Code 28-4039-31  
Name White baffle



Product Code 28-4208-30  
Name Honeycomb  
Finishing Black painted



Product Code 28-4065-47  
Name Prismatic spread lens , to be used only instead of included closing screen



Product Code 28-4065-61  
Name Frosted glass, to be used only instead of included closing screen



Product Code 28-4065-103  
Name Elliptical spread lens, to be used only instead of included closing screen



Product Code 81-04003  
Name Driver 350mA DALI dimmable



Product Code 81-04010  
Name Driver 350mA dimmable on the mains  
Description Max 1 fitting



Product Code 81-04090  
Name Driver 350mA Wireless Bluetooth