


**Perfetto-IN 80 Tiltable with
lens 8,7W 2700K CRI90 21°**

Design:



IP 43 IK 08



Product Code	Color
268-069CYN-16	Black

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Tiltable downlight, designed for COB LEDs, with PMMA lens and frosted thermoplastic screen. It features a rearward optic for a high visual comfort. Integrated snoot in black thermoplastic material. LED drivers should be ordered separately; the wattage of the fittings changes, depending on the selected driver.
Applications	Showrooms , Retail , Residential , Hospitality

Lighting specifications**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 766lm 8,7W 2700K CRI90
Nominal lumens on thermal regime (lm)	766
LOR	86
Delivered lumen (lm)	659
Watt source (W)	8.7
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	PMMA lens
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	30° tilting.
Light beam	21° Lens

Weight and dimension

Height (mm)	84
Diameter (mm)	82
Cutout diameter (mm)	75
Recessed depth (mm)	85
Weight (Kg)	0.4
False ceiling thickness (mm)	1-30

Accessories



Product Code 28-4163-30
Name Honeycomb
Finishing Black painted



Product Code 81-04027
Name Driver 700mA dimmable on the mains



Product Code 81-04028
Name Driver 700mA dimmable DALI
Description For a correct installation, please consider a ceiling recessed depth of 200mm.



Product Code 81-04088
Name Driver 700mA Wireless Bluetooth