Perfetto-IN 90 Rotatable and tiltable Dim to Warm 38°

Design:

h 85 mm   ø 84 mm   0,4 Kg

IP 20   IK 08

Product Code	Color
263-049MXN-16	Black

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Rotatable and tiltable downlight, designed for COB LEDs, with Dim to Warm technology for the regulation of the luminous intensity. The lumen value refers to the maximum dimming. The rearward optic guarantees a high visual comfort. Integrated snoot in black thermoplastic material. Professional optic devices for better visual comfort are available on demand. LED drivers should be ordered separately.
Applications	Showrooms , Residential , Hospitality

Lighting specifications

ⓘ Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1130lm 12W 1800-2700K Dim to Warm CRI 90
Nominal lumens on thermal regime (lm)	1130
LOR	56
Delivered lumen (lm)	633
Watt source (W)	12
Color temperature (K)	1800-2700K Dim to Warm
CRI	CRI 90
Lamp type	LED COB - Dim to Warm
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	5

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	350° rotation and 30° tilting
Light beam	38° Refl.

Ivela srl – member of Starlight Group

Via B. Buozzi, 15
20050 Liscate • Milano
T +39 02 9500121 • F +39 02 95001205

Documento generato il 19 May 2024
Ore 08:33:04
Pagina 1 di 2
www.ivela.it

Weight and dimension

Height (mm)	85
Diameter (mm)	92
Cutout diameter (mm)	84
Recessed depth (mm)	85
Weight (Kg)	0.4
False ceiling thickness (mm)	1-30

Accessories

Product Code	28-4163-30	
Name	Honeycomb	
Finishing	Black painted	

Product Code	28-3905-47
Name	Closing screen in clear thermoplastic

Product Code	28-4074-47
Name	Prismatic spread lens

Product Code	28-4073-61
Name	Frosted glass

Product Code	28-4073-103
Name	Elliptical spread lens

Product Code	28-4318-21
Name	Mat white square frame

Product Code	28-4181-21
Name	Mat white twin round frame

Product Code	81-04010
Name	Driver 350mA dimmable on the mains
Description	Max 1 fitting

Product Code	81-04003
Name	Driver 350mA DALI dimmable

Product Code	81-04090
Name	Driver 350mA Wireless Bluetooth

Ivela srl – member of Starlight Group

Via B. Buozzi, 15
20050 Liscate • Milano
T +39 02 9500121 • F +39 02 95001205

Documento generato il19 May 2024
Ore 08:33:04
Pagina 2 di 2
www.ivela.it