


Microperfetto Large LKM 29W 2700K CRI90 20°

Design: Ivela Design Team



IP 20



| Product Code | Color |
|--------------|-------|
| 780-269CY-16 | Black |

General specifications

| | |
|----------------------|--|
| Product type | Track lights |
| Mounting type | LKM 3-phase track DALI |
| Mounting location | Ceiling |
| Indoor/Outdoor light | Indoor |
| Description | Spotlight for LKM 3-phase electrified tracks, specially developed for high efficiency COB LED. It's equipped with integrated black snoot and solite. The spotlight is provided with adapter. |
| Applications | Showrooms , Retail , Residential , Museums , Hospitality |

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

| | |
|---------------------------------------|----------------------------|
| Lamp description | LED 2980lm 29W 2700K CRI90 |
| Nominal lumens on thermal regime (lm) | 2980 |
| LOR | 80 |
| Delivered lumen (lm) | 2384 |
| System wattage (W) | 32,8 |
| Watt source (W) | 29 |
| Color temperature (K) | 2700 |
| CRI | CRI 90 |
| Lamp type | COB LED |
| Average lamp life (h) | L80B10 50.000 |

Physical specifications

| | |
|---------------------|---|
| Body | Body and gear box in die-cast aluminium |
| Finishing | Polyester painted |
| Thermal dissipation | Passive |

Electrical specifications

| | |
|---------------------|------------|
| Driver availability | Included |
| Driver mounting | Integrated |
| Voltage (V) | 220/240 |
| Frequency (Hz) | 50/60 |

Optical specifications

| | |
|--------------------|-----------|
| Light distribution | Symmetric |
| Emission | Direct |
| Light beam | 20° Refl. |

Weight and dimension

| | |
|---------------|-----|
| Length (mm) | 110 |
| Width (mm) | 163 |
| Diameter (mm) | 61 |

Accessories



| | |
|--------------|-----------------------|
| Product Code | 28-4534-47 |
| Name | Prismatic spread lens |



| | |
|--------------|---------------|
| Product Code | 28-4535-30 |
| Name | Honeycomb |
| Finishing | Black painted |