


# 751-1613BYMD-16 Perfetto Compact 18W 3000K CRI85 20°

Design: Ivela Design Team













IP 20



Product Code	Color
751-1613BYMD-16	Black
General specifications	

Product type Track lights

Mounting type LKM 3-phase track DALI

Mounting location Ceiling

Indoor/Outdoor light Indoor

Description Spotlight for LKM 3-phase electrified tracks, mains dimmable, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available.

Applications Showrooms , Shops , Retail , Museums

Lighting specifications i Stated L.O.R. and delivered lumens values are related to standard beam angle versions Lamp description LED 2400lm 18W 3000K CRI85 Nominal lumens on thermal regime (Im) 2400 LOR 72.9 1750 Delivered lumen (Im) System wattage (W) 19,4 Watt source (W) 18 Color temperature (K) 3000 CRI CRI 85 COB LED Lamp type Average lamp life (h) L80B10 50.000 Photobiological risk group RG1

## Physical specifications

Unified Glare Rating (U.G.R. <)

Body and joint in die-cast aluminium

Finishing Polyester painted

Optic device Mirror-metallized thermoplastic material

Thermal dissipation Passive

16

•

## **Electrical specifications**

Driver availability Included

Driver mounting Integrated

Dimmable Dimmable on the mains

Voltage (V) 220/240

Frequency (Hz) 50/60

#### **Optical specifications**

Via B. Buozzi, 15

Light distribution Symmetric Emission Direct

Orientation It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.

Light beam 20°

20050 Liscate • Milano T +39 02 9500121 • F +39 02 95001205



## Weight and dimension

Length (mm)	175
Height (mm)	232
Diameter (mm)	67
Weight (Kg)	1

## Accessories

A	
V	





Product Code	28-9004-30
Name	Snoot

Product Code	28-4080-30

Name Honeycomb, to be used with snoot code 28-9004-30

Product Code 28-3905-47

Name Closing screen in clear thermoplastic