


751-2613BW-21 Perfetto Compact 26W 3000K CRI85 42°

Design: Ivela Design Team

















Product Code	Color
751-2613BW-21	Mat white

General specifications

Product type Track lights

Mounting type LKM 3-phase track DALI

Mounting location Ceiling
Indoor/Outdoor light Indoor

Description Spotlight for LKM 3-phase electrified tracks, specially developed for high efficiency

COB LEDs. Optical devices for better visual comfort are available.

Applications Showrooms , Shops , Retail , Museums

Lighting specifications i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description

Nominal lumens on thermal regime (Im)

LOR

72.9

Delivered lumen (Im)

System wattage (W)

Watt source (W)

Color temperature (K)

LOB 3125Im 26W 3000K CRI85

3125

22.9

22.9

22.78

28.9

Watt source (W)

Color temperature (K)

COLOR STANCES

 Color temperature (K)
 3000

 CRI
 CRI 85

 Lamp type
 COB LED

 Average lamp life (h)
 L80B10 50.000

Photobiological risk group RG1
Unified Glare Rating (U.G.R. <) 16

Physical specifications

Body Body and joint in die-cast aluminium
Finishing Polyester painted

Optic device Mirror-metallized thermoplastic material

Thermal dissipation Passive

Electrical specifications

 Driver availability
 Included

 Driver mounting
 Integrated

 Voltage (V)
 220/240

 Frequency (Hz)
 50/60

Optical specifications

Light distribution Symmetric
Emission Direct

Orientation It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.

Light beam 42°

20050 Liscate • Milano T +39 02 9500121 • F +39 02 95001205

Weight and dimension

Via B. Buozzi, 15

 Length (mm)
 175

 Height (mm)
 232

 Diameter (mm)
 67

 Weight (Kg)
 1



Accessories







Product Code 28-9004-30
Name Snoot

Product Code 28-4080-30

Name Honeycomb, to be used with snoot code 28-9004-30

Product Code 28-3905-47

Via B. Buozzi, 15 20050 Liscate • Milano T +39 02 9500121 • F +39 02 95001205

Name Closing screen in clear thermoplastic