


**751-2613BY-16 Perfetto**  
**Compact 26W 3000K CRI85**  
**20°**

Design: Ivela Design Team



IP 20



| Product Code  | Color |
|---------------|-------|
| 751-2613BY-16 | Black |

#### General specifications

|                      |  |
|----------------------|--|
| Product type         | Track lights   |
| Mounting type        | LKM 3-phase track DALI   |
| Mounting location    | Ceiling  |
| Indoor/Outdoor light | Indoor   |
| Description          | Spotlight for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available. |
| Applications         | Showrooms , Shops , Retail , Museums   |

#### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

|                                       |                            |
|---------------------------------------|----------------------------|
| Lamp description                      | LED 3125lm 26W 3000K CRI85 |
| Nominal lumens on thermal regime (lm) | 3125                       |
| LOR                                   | 72.9                       |
| Delivered lumen (lm)                  | 2278                       |
| System wattage (W)                    | 28,9                       |
| Watt source (W)                       | 26                         |
| Color temperature (K)                 | 3000                       |
| CRI                                   | CRI 85                     |
| Lamp type                             | COB LED                    |
| Average lamp life (h)                 | L80B10 50.000              |
| Photobiological risk group            | RG1                        |
| Unified Glare Rating (U.G.R. <)       | 16                         |

#### Physical specifications

|                     |  |
|---------------------|--|
| Body                | Body and joint in die-cast aluminium     |
| Finishing           | Polyester painted                        |
| Optic device        | Mirror-metallized thermoplastic material |
| Thermal dissipation | Passive                                  |

#### Electrical specifications

|                     |            |
|---------------------|------------|
| Driver availability | Included   |
| Driver mounting     | Integrated |
| Voltage (V)         | 220/240    |
| Frequency (Hz)      | 50/60      |

#### Optical specifications

|                    |  |
|--------------------|--|
| Light distribution | Symmetric  |
| Emission           | Direct   |
| Orientation        | It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. |
| Light beam         | 20°  |

#### Weight and dimension

|               |     |
|---------------|-----|
| Length (mm)   | 175 |
| Height (mm)   | 232 |
| Diameter (mm) | 67  |
| Weight (Kg)   | 1   |



Accessories

Product Code 28-9004-30  
Name Snoot



Product Code 28-4080-30  
Name Honeycomb, to be used with snoot code 28-9004-30



Product Code 28-3905-47  
Name Closing screen in clear thermoplastic