
## IVEL ^.

## Perfetto Compact with DALI driver 26W 3000K CRI85 20°

Design: Ivela Design Team





-1850°



IP 20



Product Code	Color
751-261BYDD-16	Black
General specifications	
Product type	Track lights
Mounting type	DKM dimmable track
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Spotlight for dimmable tracks DKM with proper adapter, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available.
Applications	Showrooms , Shops , Retail , Museums
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle version
Lamp description	LED 3125lm 26W 3000K CRI85
Nominal lumens on thermal regime (Im)	3125
LOR	72.9
Delivered lumen (Im)	2278
System wattage (W)	28,7
Watt source (W)	26
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16
Physical specifications	
Body	Body and joint in die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive
<b>-</b> 1	
Electrical specifications	
Driver type	DALI
Driver availability	Included
Driver mounting	Integrated
Dimmable	DALI dimmable
Voltage (V)	220/240
Frequency (Hz)	50/60
Optical specifications	
Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Light beam	20°

## IVEL A.

Weight and	dimension
------------	-----------

Length (mm)	175
Height (mm)	232
Diameter (mm)	67
Weight (Kg)	

## Accessories

Product Code Name



Product Code	28-9004-30
Name	Snoot
Product Code	28-4080-30
Name	Honeycomb, to be used with snoot code 28-9004-30



28-3905-47 Closing screen in clear thermoplastic

Ivela srl – member of Starlight Group