
# Perfetto Compact with DALI driver 26W 3000K CRI85 42°

Design: Ivela Design Team

















Product Code	Color
--------------	-------

751-261BWDD-16 Black

#### **General specifications**

Product type Track lights

Mounting type DKM dimmable track

Mounting location Ceiling
Indoor/Outdoor light Indoor

Description Spotlight for dimmable tracks DKM with proper adapter, specially developed for high

efficiency COB LEDs. Optical devices for better visual comfort are available.

Applications Showrooms , Shops , Retail , Museums

## Lighting specifications i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp descriptionLED 3125Im 26W 3000K CRI85Nominal lumens on thermal regime (Im)3125LOR72.9Delivered lumen (Im)2278System wattage (W)28,7Watt source (W)26

Color temperature (K) 3000

CRI CRI 85

Lamp type COB LED

Average lamp life (h) L80B10 50.000

Photobiological risk group RG1
Unified Glare Rating (U.G.R. <) 16

### Physical specifications

Body and joint in die-cast aluminium

Finishing Polyester painted

Optic device Mirror-metallized thermoplastic material

Thermal dissipation Passive

#### **Electrical specifications**

Driver type DALI
Driver availability Included
Driver mounting Integrated
Dimmable DALI dimmable
Voltage (V) 220/240
Frequency (Hz) 50/60

#### **Optical specifications**

Via B. Buozzi, 15

Light distribution Symmetric
Emission Direct

Orientation It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.

Light beam 42°

20050 Liscate • Milano T +39 02 9500121 • F +39 02 95001205



#### Weight and dimension

Length (mm)	175	
Height (mm)	232	
Diameter (mm)	67	
Weight (Kg)	1	

#### Accessories

	4	
-	V	,





Product Code	28-9004-30
Name	Snoot

Product Code	28-4080-30
--------------	------------

Name Honeycomb, to be used with snoot code 28-9004-30

Product Code 28-3905-47

Name Closing screen in clear thermoplastic