


# Microperfetto Large **Broadway zoom 12,4W** 2700K

Design: Ivela Design Team













#### **Product Code** Color 787-069C-16 Black

#### **General specifications**

| Product type         | Track lights  |
|----------------------|---|
| Mounting type        | Lighting systems  |
| Mounting location    | Ceiling   |
| Indoor/Outdoor light | Indoor  |
| Description          | PWM dimmable spotlight for Broadway lighting system, equipped with a high efficiency COB LED. It features an adjustable arm with triple junction, for cardan movements on all axes, in addition to the 355° orientation of the head. It's equipped with zoom lens, seven positions adjustable and with a spotlight range from 13° to 47°, and integrated black snoot. |

Product notes Special configuration. This configuration has longer lead times, price uplifts and minimum order quantities.

Max. 5 fittings on each 1300 mm Broadway profile. Max. 10 fittings on each 2300 mm Broadway profile. Showrooms, Retail, Residential, Museums, Hospitality

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Applications

## Lighting specifications

Lamp description



| Nominal lumens on thermal regime (lm) | 1216          |
|---------------------------------------|---------------|
| LOR                                   | 67            |
| Delivered lumen (lm)                  | 815           |
| System wattage (W)                    | 14,4          |
| Watt source (W)                       | 12.4          |
| Color temperature (K)                 | 2700          |
| CRI                                   | CRI 90        |
| Lamp type                             | COB LED       |
| Average lamp life (h)                 | L80B10 50.000 |

### Physical specifications

**Electrical specifications** 

| Body                | Body and joint in die-cast aluminium |
|---------------------|--------------------------------------|
| Finishing           | Polyester painted                    |
| Optic device        | PMMA zoom lens                       |
| Thermal dissipation | Passive                              |

# Thermal dissipation

| Driver availability | Included   |
|---------------------|------------|
| Driver mounting     | Integrated |
| Voltage (V)         | 220/240    |
| Frequency (Hz)      | 50/60      |

#### **Optical specifications**

| Light distribution | Symmetric      |
|--------------------|----------------|
| Emission           | Direct         |
| Aiming             | Multidirection |
| Light beam         | 13° to 47°     |



#### Weight and dimension

| Length (mm)   | 110 |
|---------------|-----|
| Height (mm)   | 200 |
| Width (mm)    | 135 |
| Diameter (mm) | 61  |