



Perfetto In-Ground 6,5W 3000K 52°

Design:



IP 68 1mt IK 10

Product Code	Color
1455BV000	Stainless steel
General specifications	
Product type	Outdoor recessed, walk-over
Mounting location	Ground/Wall
Indoor/Outdoor light	Outdoor
Description	Ground walk-over light ideal for both indoor and outdoor, equipped with the latest generation of LEDs and with reflector. It can be installed into the floor, the wall or into the ceiling with the proper springs. Recessed housing for installation in-ground to be ordered separately. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver.
Applications	Walkways , Residential , Gardens
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle versions
Lamp description	LED 785lm 6.5W 3000K CRI80
Nominal lumens on thermal regime (lm)	785
LOR	70
Delivered lumen (lm)	550
Watt source (W)	6.5
Color temperature (K)	3000
CRI	CRI 80
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Physical specifications	
Body	Brushed stainless steel
Optic device	Mirror finished polycarbonate
Mechanical load (kg)	500
Gasket	Silicone
Safety glass	Tempered and bevelled (8mm)
Electrical specifications	
Cable gland	M12,5 in nickel-plated brass, complete with 2 mt cable
Supply cable	H05RN-F 2x1 mm², 2 mt. length
Optical specifications	
Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	52°
Weight and dimension	
Height (mm)	77
Diameter (mm)	58
Weight (Kg)	0.7

Accessories


Product Code 28-4200-30
Name Honeycomb
Finishing Black painted



Product Code 28-4177-4730
Name Black silk-screened clear glass, with an anti-dazzling and an asymmetric effect



Product Code 28-4177-47
Name Prismatic spread lens



Product Code 28-4195-30
Name Recessed housing for installation in-ground
Diameter (mm) 74



Product Code 28-4197-48
Name Springs for false ceiling and panelling mounting min.1mm max15mm.



Product Code 160821
Name 10mt Supply cable coil, H05RN-F 2x1 mm²



Product Code 84108
Name IP 68 rated cable connector
IP rating IP 68



Product Code 81-04065
Name Driver 700mA (IP67)