


Perfetto-IN 70 12W 3000K CRI90 21°

Design:













IP 43 IK 08



Produc	ct Code
262-03	9BNY-16
Genera	al specifications
Mounti	ng type
Indoor/	Outdoor light
Descrip	otion
Applica	itions
Lightin	g specifications
Lamp o	lescription
Nomina	al lumens on therm
LOR	
Deliver	ed lumen (lm)
Watt so	ource (W)
Color te	emperature (K)

Ð	W850°
42	11



Physical specifications Body

Die-cast aluminium Polyester painted Finishina Optic device Mirror-metallized thermoplastic material

Thermal dissipation Passive

Electrical specifications

Driver availability Separate Driver mounting Separate

Dimmable Dimmable on the mains / DALI dimmable

Optical specifications

Emission Aiming Fixed Light beam 21°

Weight and dimension

83 70 64 83 0.3 1-30

Color Black

unting type Ceiling - recessed

oor/Outdoor light Indoor

Fixed downlight designed for COB LEDs, featuring a rearward optic for a high visual scription comfort. Inner snoot in black thermoplastic material. LED drivers should be ordered

separately, the wattage of the fittings changes depending on the selected driver.

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Commercial areas , Showrooms , Residential , Hospitality

LED 1470lm 12W 3000K CRI90

ninal lumens on thermal regime (lm) 1470

58 ivered lumen (lm) 853

tt source (W) 12 or temperature (K) 3000 CRI CRI 90 Lamp type COB LED

L80B10 50.000 Average lamp life (h)

Photobiological risk group RG1 Unified Glare Rating (U.G.R. <)

Closing screen Clear thermoplastic material

Light distribution Symmetric Direct

Via B. Buozzi, 15

Height (mm) Diameter (mm) Cutout diameter (mm) Recessed depth (mm) Weight (Kg) False ceiling thickness (mm)



Accessories



Product Code 28-4039-100

Name Satined gold baffle



Product Code 28-4039-31
Name White baffle



Product Code 28-4208-30
Name Honeycomb
Finishing Black painted



Product Code 28-4065-47

Name Prismatic spread lens , to be used only instead of included closing screen



Product Code 28-4065-61

Name

Frosted glass, to be used only instead of included closing screen



Product Code 28-4065-103

Name

Elliptical spread lens, to be used only instead of included closing screen



Product Code 81-04003

Name Driver 350mA DALI dimmable



Product Code 81-04010

Name Driver 350mA dimmable on the mains

Description Max 1 fitting