


**Perfetto-IN 90 Rotatable
and tiltable IP66 with lens
8,7W 3000K CRI90 38°**

Design:



IP 66 IK 08



Product Code	Color
266-069BWN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor - Outdoor
Description	Rotatable and tiltable downlight, featuring a rearward optic for high visual comfort and replaceable PMMA lenses for different light beams. Integrated snoot in black thermoplastic material. LED drivers should be ordered separately.
Applications	Showrooms , Retail , Residential , Hospitality

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 809lm 8,7W 3000K CRI90
Nominal lumens on thermal regime (lm)	809
LOR	86
Delivered lumen (lm)	696
Watt source (W)	8.7
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	PMMA lens
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable

Optical specifications


Light distribution	Symmetric
Emission	Direct
Orientation	350° rotation and 30° tilting
Aiming	Rotatable / tiltable
Light beam	38° Lens

Weight and dimension


Height (mm)	105
Diameter (mm)	92
Cutout diameter (mm)	84
Recessed depth (mm)	105
Weight (Kg)	0.5
False ceiling thickness (mm)	1-30

Accessories

Product Code	84108
Name	IP 68 rated cable connector
IP rating	IP 68



Product Code	28-4318-21
Name	Mat white square frame



Product Code	28-4181-21
Name	Mat white twin round frame



Product Code	28-4163-30
Name	Honeycomb
Finishing	Black painted



Product Code	81-04032
Name	Driver 700mA (IP68)



Product Code	81-04034
Name	Driver 700mA DALI IP68



Product Code	81-04027
Name	Driver 700mA dimmable on the mains



Product Code	81-04028
Name	Driver 700mA dimmable DALI
Description	For a correct installation, please consider a ceiling recessed depth of 200mm.



Product Code	81-04088
Name	Driver 700mA Wireless Bluetooth