


## Microperetto IP66 8,7W 48Vdc 2700K 21°

Design:



0,5 Kg



IP 66 IK 10



| Product Code  | Color  |
|---|--|
| 1912CY0030  | Black  |
| <b>General specifications</b>   |  |
| Product type  | Outdoor spotlight  |
| Mounting location   | Ground   |
| Indoor/Outdoor light  | Outdoor  |
| Description   | Exterior spotlight equipped with COB LED and frosted lens, for outdoor applications in the ground, with a spike or a bracket. It's easy to install and it guarantees, thanks to the special antioxidising treatment and the silicone gaskets, a high protection rating IP66. Bracket in AISI 304 steel, polyester painted.<br>The spotlight is provided with integrated 48Vdc converter. Electronic transformers for remote use 81-04054 (PWM) e 81-04055 (On/Off) to be ordered separately. |
| Product notes   | Special configuration. This configuration has longer lead times, price uplifts and minimum order quantities.   |
| Applications  | Squares , Gardens , Façades , Courtyards   |
| <b>Lighting specifications</b>  |  |
| <span style="color: yellow;">i</span> Stated L.O.R. and delivered lumens values are related to standard beam angle versions |  |
| Lamp description  | LED 925lm 8,7W 2700K CRI85   |
| Nominal lumens on thermal regime (lm)   | 925  |
| LOR   | 88   |
| Delivered lumen (lm)  | 773  |
| Watt source (W)   | 8.7  |
| Color temperature (K)   | 2700   |
| CRI   | CRI 85   |
| Lamp type   | COB LED  |
| Average lamp life (h)   | L80B10 50.000  |
| <b>Physical specifications</b>  |  |
| Body  | Die-cast aluminium and thermoplastic material  |
| Finishing   | Polyester painted, with a special antioxidising pretreatment   |
| Optic device  | PMMA lens  |
| Gasket  | Silicone   |
| Safety glass  | Grinded, tempered and heat resistant glass   |
| Screws  | Stainless steel A4   |
| <b>Electrical specifications</b>  |  |
| Driver availability   | Separate   |
| Driver mounting   | Separate   |
| 48VDC electronic transformer availability   | Not included   |
| 48VDC electronic transformer mounting   | Separate   |
| Converter CV - CC availability  | Included   |
| Converter CV - CC mounting  | Integrated   |
| Voltage (V)   | 48   |
| Supply cable  | H05RN-F 2x1 mm <sup>2</sup> , 2 mt. length with rated cable connector  |
| <b>Optical specifications</b>   |  |
| Light distribution  | Symmetric  |
| Emission  | Direct   |
| Aiming  | Fixed  |
| Light beam  | 21°  |

**Weight and dimension**

|               |     |
|---------------|-----|
| Length (mm)   | 105 |
| Diameter (mm) | 53  |
| Weight (Kg)   | 0.5 |

**Accessories**

|              |            |
|--------------|------------|
| Product Code | 28-4499-30 |
| Name         | Honeycomb  |



|              |                  |
|--------------|------------------|
| Product Code | 28-4445-30       |
| Name         | Asymmetric snout |



|              |                           |
|--------------|---------------------------|
| Product Code | 28-2377-30                |
| Name         | Black thermoplastic spike |



|              |   |
|--------------|---|
| Product Code | 81-04054  |
| Name         | 150W 220/240V / 48Vdc electronic transformer for remote use - PWM |



|              |  |
|--------------|--|
| Product Code | 81-04055   |
| Name         | 150W 220/240V 48Vdc electronic transformer for remote use - On/Off |