


Minirooler-IN 15 lights

3000K CRI90 14°+41°

Design: Ivela Design Team



IP 40



| Product Code | Color |
|---------------|-----------|
| 273-019BQN-21 | Mat white |

General specifications

| | |
|----------------------|---|
| Product type | Downlights |
| Mounting type | Ceiling - recessed |
| Indoor/Outdoor light | Indoor |
| Description | Fixed miniaturized linear downlight, featuring 15 high-efficiency LEDs of the latest generation. It grants high lighting performance, low glare levels and homogeneous light distribution. LED drivers should be ordered separately; the wattage of the fittings changes, depending on the selected driver. |
| Applications | Offices , Residential , Shops , Showrooms , Hospitality |

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

| | |
|---------------------------------------|------------------------------|
| Lamp description | LED 1800lm 17,5W 3000K CRI90 |
| Nominal lumens on thermal regime (lm) | 1800 |
| LOR | 69 |
| Delivered lumen (lm) | 1242 |
| Watt source (W) | 17.5 |
| Color temperature (K) | 3000 |
| CRI | CRI 90 |
| Lamp type | COB LED |
| Average lamp life (h) | L80B10 50.000 |
| Unified Glare Rating (U.G.R. <) | 5 |

Physical specifications

| | |
|---------------------|---------------------|
| Body | Die-cast aluminium |
| Finishing | Polyester painted |
| Optic device | 15 PMMA microlenses |
| Thermal dissipation | Passive |

Electrical specifications

| | |
|---------------------|-----------------------|
| Driver availability | Separate |
| Driver mounting | Separate |
| Dimmable | DALI - Dimmable 1-10V |

Optical specifications

| | |
|--------------------|---------------|
| Light distribution | Symmetric |
| Emission | Direct |
| Aiming | Fixed |
| Light beam | 14°+41° Long. |

Weight and dimension

| | |
|---------------------|-----|
| Length (mm) | 198 |
| Width (mm) | 23 |
| Recessed depth (mm) | 50 |
| Weight (Kg) | 0.3 |

Accessories

Product Code 81-04077
Name Driver SLIM 400mA
Description Installation through the recessed hole. For a correct installation consider a ceiling recessed depth of h.140mm x l.120mm

Product Code 81-04080
Name Driver SLIM 400mA DALI Dimmable

Product Code 81-04083
Name Driver SLIM 400mA 1-10V dimmable



Product Code 81-02571
Name Driver 400mA



Product Code 81-02565
Name Driver 400mA DALI dimmable



Product Code 81-04057
Name Driver 400mA 1-10V dimmable