


Minirooler-IN 15 lights

2700K CRI90 50°

Design: Ivela Design Team



IP 40



Product Code	Color
273-019CVN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed miniaturized linear downlight, featuring 15 high-efficiency LEDs of the latest generation. It grants high lighting performance, low glare levels and homogeneous light distribution. LED drivers should be ordered separately; the wattage of the fittings changes, depending on the selected driver.
Applications	Offices , Residential , Shops , Showrooms , Hospitality

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1800lm 17,5W 2700K CRI90
Nominal lumens on thermal regime (lm)	1800
LOR	80
Delivered lumen (lm)	1080
Watt source (W)	17.5
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Unified Glare Rating (U.G.R. <)	5

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	15 PMMA microlenses
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI - Dimmable 1-10V

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	50°

Weight and dimension

Length (mm)	198
Width (mm)	23
Recessed depth (mm)	50
Weight (Kg)	0.3

Accessories

Product Code	81-04077
Name	Driver SLIM 400mA
Description	Installation through the recessed hole. For a correct installation consider a ceiling recessed depth of h.140mm x l.120mm

Product Code	81-04080
Name	Driver SLIM 400mA DALI Dimmable

Product Code	81-04083
Name	Driver SLIM 400mA 1-10V dimmable



Product Code	81-02571
Name	Driver 400mA



Product Code	81-02565
Name	Driver 400mA DALI dimmable



Product Code	81-04057
Name	Driver 400mA 1-10V dimmable