IVEL ^.

Perfetto IP66 30W 3000K

42°

Design:



| 147 72 | <u>4</u> | |
|-----------|----------|--------|
| 90° | | 1,4 Kg |

C€ ∰ ⊕ ≟

IP 66 IK 10



| Product Code | Color | |
|---------------------------------------|--|--|
| 1037BW0030 | Black | |
| General specifications | | |
| Product type | Outdoor spotlight | |
| Mounting location | Ground, wall or ceiling | |
| Indoor/Outdoor light | Outdoor | |
| Description | Exterior spotlight equipped with COB LED, suitable for outdoor applications where a powerful and ecological light is needed. It can be mounted on the wall/ceiling or in t ground through the specific spike. High protection rating IP66. | |
| Applications | Squares , Gardens , Façades , Courtyards | |
| Lighting specifications | i Stated L.O.R. and delivered lumens values are related to standard beam angle version | |
| Lamp description | LED 3500lm 30W 3000K CRI85 | |
| Nominal lumens on thermal regime (Im) | 3500 | |
| LOR | 74.1 | |
| Delivered lumen (lm) | 2594 | |
| System wattage (W) | 32,1 | |
| Watt source (W) | 30 | |
| Color temperature (K) | 3000 | |
| CRI | CRI 85 | |
| Lamp type | COB LED | |
| Average lamp life (h) | L80B10 50.000 | |
| Photobiological risk group | RG1 | |
| Physical specifications | | |
| Body | Die-cast aluminium | |
| Finishing | Polyester painted, with a special antioxidising pretreatment | |
| Optic device | Mirror-metallized thermoplastic material | |
| Gasket | Silicone | |
| Safety glass | Grinded, tempered 3 mm, and heat resistant glass | |
| Screws | Stainless steel | |
| Electrical specifications | | |
| Driver availability | Included | |
| Driver mounting | Integrated | |
| Voltage (V) | 220/240 | |
| Frequency (Hz) | 50/60 | |
| Cable gland | Nickel-plated brass M16x1,5 | |
| Supply cable | H05RN-F 3x1 mm ² , 2 mt. length | |
| Optical specifications | | |
| Light distribution | Symmetric | |
| Emission | Direct | |
| Orientation | It pivots up to 90° upwards. | |
| | | |
| Aiming | Tiltable | |

IVEL ^.

Weight and dimension

| Height (mm) | 241 |
|---------------|-----|
| Diameter (mm) | 72 |
| Weight (Kg) | 1.4 |

28-4130-30

Accessories

Product Code















| Name | Asymmetric snoot |
|--------------|-----------------------------|
| | |
| Product Code | 28-4208-30 |
| Name | Honeycomb |
| Finishing | Black painted |
| Product Code | 28-04191-47 |
| Name | Prismatic spread lens |
| | |
| Product Code | 84108 |
| Name | IP 68 rated cable connector |
| IP rating | IP 68 |
| | ~~~~~ |
| Product Code | 28-2377-30 |
| Name | Black thermoplastic spike |
| | |
| Product Code | 28-4163-30 |
| Name | Honeycomb |
| Finishing | Black painted |
| Product Code | 28-04190-47 |
| Name | Prismatic spread lens |
| Nume | i nomalic opieau ieno |