


## Microperfetto Low-R 3000K 18W 16°

Design:



IP 20



### Product Code

756-679BZN-16

### Color

Black

### General specifications

Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Spotlight with prismatic spread lens and canopy for recessed application, specially developed for high efficiency COB LEDs. Optic devices for different beam angles and optical devices for better visual comfort are available on demand. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver.
Applications	Retail , Residential , Hospitality

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 2051lm 18W 3000K CRI90
Nominal lumens on thermal regime (lm)	2051
LOR	70
Delivered lumen (lm)	1436
Watt source (W)	18
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16

### Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

### Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI dimmable

### Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 330° around the vertical axis and pivot up to 90° upwards.
Light beam	16° Refl.

### Weight and dimension

Length (mm)	75
Height (mm)	95
Width (mm)	53
Cutout diameter (mm)	55
Recessed depth (mm)	50
Weight (Kg)	0.4

**Accessories**

---



Product Code 28-4139-100  
Name Satined gold baffle



Product Code 28-4163-30  
Name Honeycomb  
Finishing Black painted



Product Code 28-4073-103  
Name Elliptical spread lens



Product Code 81-04011  
Name Driver 500mA



Product Code 81-04002  
Name Driver 500mA DALI dimmable