


Microperfetto Low-R 2700K 18W 16°

Design:



IP 20



Product Code

756-679CZN-21

Color

Mat white

General specifications

Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Spotlight with prismatic spread lens and canopy for recessed application, specially developed for high efficiency COB LEDs. Professional optic devices for different beam angles and optical devices for better visual comfort are available on demand. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver.

Applications

Retail , Residential , Hospitality

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1946lm 18W 2700K CRI90
Nominal lumens on thermal regime (lm)	1946
LOR	70
Delivered lumen (lm)	1362
Watt source (W)	18
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 330° around the vertical axis and pivot up to 90° upwards.
Light beam	16° Refl.

Weight and dimension


Length (mm)	75
Height (mm)	95
Width (mm)	53
Cutout diameter (mm)	55
Recessed depth (mm)	50
Weight (Kg)	0.4

Accessories

Product Code	28-4139-100
Name	Satined gold baffle



Product Code	28-4139-31
Name	White baffle



Product Code	28-4163-30
Name	Honeycomb
Finishing	Black painted



Product Code	28-4073-103
Name	Elliptical spread lens



Product Code	81-04011
Name	Driver 500mA



Product Code	81-04002
Name	Driver 500mA DALI dimmable