

Microperfetto Cupcake 2700K 18W 45°

Design:















IP 20



Product Code	Color
758-679CVN-21	Mat white
General specifications	
Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Spotlight with prismatic spread lens for surface installation, specially developed for high efficiency COB LEDs. Professional optic devices for better visual comfort are available. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver.
Applications	Showrooms , Shops , Residential , Accommodation facilities
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle versions
Lamp description	LED 1946lm 18W 2700K CRI90
Nominal lumens on thermal regime (Im)	1946
LOR	70
Delivered lumen (Im)	1362
Watt source (W)	18
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16
Physical specifications	
Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive
Electrical specifications	
Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI dimmable
Optical specifications	
Light distribution	Symmetric
Emission	Direct

45°

75

53

42 50

0.2

Light beam

Height (mm)

Diameter (mm)

Weight (Kg)

Weight and dimension

Cutout diameter (mm)

Recessed depth (mm)



Accessories









Product Code 28-4139-100

Name Satined gold baffle

Product Code 28-4139-31
Name White baffle

Product Code 28-4163-30
Name Honeycomb
Finishing Black painted

Product Code 28-4073-103

Name Elliptical spread lens

Product Code 81-04046
Name Driver 500mA

Product Code 81-04026

Name Driver 500mA DALI

Description For a correct installation, consider a ceiling recessed depth of 200mm