


Microperfetto Cupcake

2700K 18W 45°

Design:



IP 20



| Product Code | Color |
|---------------|-------|
| 758-679CVN-16 | Black |

General specifications

| | |
|----------------------|--|
| Product type | Semi- recessed surface spotlights |
| Mounting type | Ceiling - recessed |
| Indoor/Outdoor light | Indoor |
| Description | Spotlight with prismatic spread lens for surface installation, specially developed for high efficiency COB LEDs. Professional optic devices for better visual comfort are available. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver. |

Product notes

Applications Showrooms , Shops , Residential , Accommodation facilities

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

| | |
|---------------------------------------|----------------------------|
| Lamp description | LED 1946lm 18W 2700K CRI90 |
| Nominal lumens on thermal regime (lm) | 1946 |
| LOR | 70 |
| Delivered lumen (lm) | 1362 |
| Watt source (W) | 18 |
| Color temperature (K) | 2700 |
| CRI | CRI 90 |
| Lamp type | COB LED |
| Average lamp life (h) | L80B10 50.000 |
| Photobiological risk group | RG1 |
| Unified Glare Rating (U.G.R. <) | 16 |

Physical specifications

| | |
|---------------------|--|
| Body | Die-cast aluminium |
| Finishing | Polyester painted |
| Optic device | Mirror-metallized thermoplastic material |
| Thermal dissipation | Passive |

Electrical specifications

| | |
|---------------------|---------------|
| Driver availability | Separate |
| Driver mounting | Separate |
| Dimmable | DALI dimmable |

Optical specifications

| | |
|--------------------|-----------|
| Light distribution | Symmetric |
| Emission | Direct |
| Light beam | 45° |

Weight and dimension


| | |
|----------------------|-----|
| Height (mm) | 75 |
| Diameter (mm) | 53 |
| Cutout diameter (mm) | 42 |
| Recessed depth (mm) | 50 |
| Weight (Kg) | 0.2 |

Accessories

Product Code 28-4139-100
Name Satined gold baffle



Product Code 28-4139-31
Name White baffle



Product Code 28-4163-30
Name Honeycomb
Finishing Black painted



Product Code 28-4073-103
Name Elliptical spread lens



Product Code 81-04046
Name Driver 500mA

Product Code 81-04026
Name Driver 500mA DALI
Description For a correct installation, consider a ceiling recessed depth of 200mm