IVEL ^.

Microperfetto Cupcake 3000K 18W 45°





| 53 | | | |
|------------|-------------|---------|--------|
| \bigcirc | h 50 mm | ø 42 mm | 0,2 Kg |



IP 20



| Product Code | Color | |
|---------------------------------------|---|--|
| 758-679BVN-21 | Mat white | |
| General specifications | | |
| Product type | Semi- recessed surface spotlights | |
| Mounting type | Ceiling - recessed | |
| Indoor/Outdoor light | Indoor | |
| Description | Spotlight with prismatic spread lens for surface installation, specially developed for high efficiency COB LEDs. Professional optic devices for better visual comfort are available. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver. | |
| Applications | Showrooms , Shops , Residential , Accommodation facilities | |
| Lighting specifications | i Stated L.O.R. and delivered lumens values are related to standard beam angle versi | |
| Lamp description | LED 2051lm 18W 3000K CRI90 | |
| Nominal lumens on thermal regime (Im) | 2051 | |
| LOR | 70 | |
| Delivered lumen (lm) | 1436 | |
| Watt source (W) | 18 | |
| Color temperature (K) | 3000 | |
| CRI | CRI 90 | |
| Lamp type | COB LED | |
| Average lamp life (h) | L80B10 50.000 | |
| Photobiological risk group | RG1 | |
| Unified Glare Rating (U.G.R. <) | 16 | |
| Physical specifications | | |
| Body | Die-cast aluminium | |
| Finishing | Polyester painted | |
| Optic device | Mirror-metallized thermoplastic material | |
| Thermal dissipation | Passive | |
| Electrical specifications | | |
| Driver availability | Separate | |
| Driver mounting | Separate | |
| Dimmable | DALI dimmable | |
| Optical specifications | | |
| Light distribution | Symmetric | |
| Emission | Direct | |
| Light beam | 45° | |
| Weight and dimension | | |
| Height (mm) | 75 | |
| Diameter (mm) | 53 | |
| Cutout diameter (mm) | 42 | |
| Recessed depth (mm) | 50 | |
| | | |

IVEL A.

Accessories









| Product Code |
|--------------|
| Name |

Product Code Name

Product Code Name Finishing

Product Code Name

Product Code Name

Product Code Name Description

28-4139-100 Satined gold baffle 28-4139-31 White baffle 28-4163-30 Honeycomb Black painted 28-4073-103 Elliptical spread lens 81-04046 Driver 500mA

> 81-04026 Driver 500mA DALI For a correct installation, consider a ceiling recessed depth of 200mm