


# Microperfetto Cupcake 3000K 18W 45°

Design:















IP 20



Product Code	Color
758-679BVN-16	Black
General specifications	
Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Spotlight with prismatic spread lens for surface installation, specially developed for high efficiency COB LEDs. Professional optic devices for better visual comfort are available. LED drivers should be ordered separately; the wattage of the fittings changes depending on the selected driver.
Product notes	
Applications	Showrooms , Shops , Residential , Accommodation facilities
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle versions
Lamp description	LED 2051lm 18W 3000K CRI90
Nominal lumens on thermal regime (lm)	2051
LOR	70
Delivered lumen (lm)	1436
Watt source (W)	18
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED

L80B10 50.000

RG1

16

### Physical specifications

Photobiological risk group

Unified Glare Rating (U.G.R. <)

Average lamp life (h)

Body	Die-cast aluminium
Finishing	Polyester painted
Ontic device	Mirror-metallized th

Optic device Mirror-metallized thermoplastic material

Thermal dissipation Passive

## **Electrical specifications**

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI dimmable

#### Optical specifications

Light distribution	Symmetric
Emission	Direct
Light beam	45°

### Weight and dimension

Via B. Buozzi, 15

Height (mm)	75
Diameter (mm)	53
Cutout diameter (mm)	42
Recessed depth (mm)	50
Weight (Kg)	0.2



#### Accessories











Product Code 28-4139-100
Name Satined gold baffle

Product Code 28-4139-31
Name White baffle

Product Code 28-4163-30
Name Honeycomb
Finishing Black painted

Product Code 28-4073-103

Name Elliptical spread lens

 Product Code
 81-04046

 Name
 Driver 500mA

Product Code 81-04026

Name Driver 500mA DALI

Description For a correct installation, consider a ceiling recessed depth of 200mm