
## IVEL ^.

### Microperfetto Cupcake Dim

### to Warm 12W 45°







-\\850°

CE ∰ @

IP 20



Product Code	Color
762-049MVN-21	Mat white
General specifications	
Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Spotlight with prismatic spread lens and canopy for recessed application, spec developed for high-efficiency COB LEDs with Dim to Warm technology for mana the colour temperature through the regulation of the luminous intensity. Professio optic devices for better visual comfort are available on demand. Remote LED dri should be ordered separately; the wattage of the fittings changes depending on selected driver.
Applications	Showrooms , Shops , Residential , Accommodation facilities
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle vers
Lamp description	LED 1130lm 12W 1800-2700K Dim to Warm CRI 90
Nominal lumens on thermal regime (Im)	1130
LOR	70
Delivered lumen (lm)	791
Watt source (W)	12
Color temperature (K)	1800-2700K Dim to Warm
CRI	CRI 90
Lamp type	LED COB - Dim to Warm
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16
Physical specifications	
Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive
Electrical specifications	
Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable
Optical specifications	
Light distribution	Symmetric
Emission	Direct
Light beam	45°
Weight and dimension	
Height (mm)	75
Diameter (mm)	53
Cutout diameter (mm)	42
Recessed depth (mm)	50
Weight (Kg)	0.2

# IVEL ^.

#### Accessories











6

Ċ

Ð

D

Product Code Name

> Product Code Name

Product Code Name Finishing

Product Code Name

Product Code Name

Product Code Name Description

Product Code Name

Product Code Name 28-4139-31 White baffle 28-4163-30 Honeycomb

28-4139-100

Satined gold baffle

Black painted

28-4073-61 Frosted glass

28-4073-103 Elliptical spread lens

81-04010 Driver 350mA dimmable on the mains Max 1 fitting

81-04003 Driver 350mA DALI dimmable

81-04090 Driver 350mA Wireless Bluetooth