


Microperfetto Large-R with lens 29W 2700K CRI90 21°

Design: Ivela Design Team



IP 20



Product Code	Color
785-279CZN-21	Mat white

General specifications

Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Spotlight specially developed for high-efficiency COB LEDs. It's equipped with silicone lens. Black snoot and solite are integrated. Electronic transformer for remote use and proper dimmer to be ordered separately.
Applications	Showrooms , Retail , Residential , Museums , Hospitality

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 2980lm 29W 2700K CRI90
Nominal lumens on thermal regime (lm)	2980
LOR	85
Delivered lumen (lm)	2533
Watt source (W)	29
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Silicone lens
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI - Dimmable 1-10V

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 330° about vertical axis and pivot up to 90° upwards.
Light beam	21° Lens

Weight and dimension

Length (mm)	131
Height (mm)	110
Diameter (mm)	61
Cutout diameter (mm)	55
Recessed depth (mm)	50

Accessories



Product Code 28-4535-30
Name Honeycomb
Finishing Black painted



Product Code 81-04069
Name Driver 800mA

Product Code
Name



Product Code 81-04071
Name Driver 800mA Dimmable 1-10V