


Microperfetto Large-R with lens 29W 2700K CRI90 21°

Design: Ivela Design Team















IP 20



| Product Code | Color |
|------------------------|-----------------------------------|
| 785-279CZN-16 | Black |
| General specifications | |
| Product type | Semi- recessed surface spotlights |
| Mounting type | Ceiling - recessed |

Mounting location Ceiling
Indoor/Outdoor light Indoor

Description

Spotlight specially developed for high-efficiency COB LEDs. It's equipped with silicone lens. Black snoot and solite are integrated. Electronic transformer for remote use and proper dimmer to be ordered separately.

Applications Showrooms , Retail , Residential , Museums , Hospitality

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description

LED 2980Im 29W 2700K CRI90

Nominal lumens on thermal regime (Im) 2980 LOR 85 Delivered lumen (Im) 2533 Watt source (W) 29 Color temperature (K) 2700 CRI CRI 90 COB LED Lamp type L80B10 50.000 Average lamp life (h)

Physical specifications

Body Die-cast aluminium
Finishing Polyester painted
Optic device Silicone lens
Thermal dissipation Passive

Electrical specifications

Driver availability Separate
Driver mounting Separate

Dimmable DALI - Dimmable 1-10V

Optical specifications

Light distribution Symmetric
Emission Direct

Orientation It can rotate up to 330° about vertical axis and pivot up to 90° upwards.

Light beam 21° Lens

Weight and dimension

 Length (mm)
 131

 Height (mm)
 110

 Diameter (mm)
 61

 Cutout diameter (mm)
 55

 Recessed depth (mm)
 50



Accessories



Product Code
Name
Finishing

28-4535-30 Honeycomb Black painted

 Product Code
 81-04069

 Name
 Driver 800mA

Product Code

Name

Product Code

81-04071

Name Driver 800mA Dimmable 1-10V