
IVEL A.

754-889CV-21 Microperfetto 48 VDC 26W 2700K DALI **45°**

Design:





IP 20



Product Code	Color	
754-889CV-21	Mat white	
On demand	Yes	
General specifications		
Product type	Track lights	
Mounting type	48V low-voltage electrified tracks	
Mounting location	Ceiling	
Indoor/Outdoor light	Indoor	
Description	Spotlight for 48VDC low voltage electrified tracks specially developed for high efficiency COB LED, with prismatic spread lens. The deeply-recessed optics and the standard snoot make it ideal to reduce glare to the minimum. The spotlight is provider with an adapter, with an integrated CV-CC converter. DALI electronic transformer for remote use for the 48VDC track to be ordered separately. Replaceable optical accessories are available on demand.	
Applications	Showrooms , Retail , Residential , Museums , Hospitality	
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle version	
Lamp description	LED 2590lm 26W 2700K CRI90	
Nominal lumens on thermal regime (Im)	2590	
LOR	70	
Delivered lumen (Im)	1813	
System wattage (W)	30,3	
Watt source (W)	26	
Color temperature (K)	2700	
CRI	CRI 90	
Lamp type	COB LED	
Average lamp life (h)	L80B10 50.000	
Photobiological risk group	RG1	
Unified Glare Rating (U.G.R. <)	16	
Physical specifications		
Body	Die-cast aluminium	
Finishing	Polyester painted	
Optic device	Mirror-metallized thermoplastic material	
Thermal dissipation	Passive	

Electrical specifications

Electrical specifications	
Driver availability	Included
Driver mounting	Integrated
48VDC electronic transformer availability	Not included
48VDC electronic transformer mounting	Separate
Converter CV - CC availability	Included
Converter CV - CC mounting	Integrated
Dimmable	PWM
Voltage (V)	48

Ivela srl – member of Starlight Group

Via B. Buozzi, 15 20050 Liscate • Milano T +39 02 9500121 • F +39 02 95001205

IVEL ^.

Optical specifications

Light distribution	Symmetric	
Emission	Direct	
Light beam	45°	
Weight and dimension		
Length (mm)	95	
Height (mm)	116	
Width (mm)	150	

53

0.4

Diameter (mm)

Weight (Kg)

|--|



÷.

Product Code	28-4163-30
Name	Honeycomb
Finishing	Black painted
Product Code	28-4139-100
Name	Satined gold baffle
Product Code	28-4139-31
Name	White baffle
Product Code	28-4073-61
Name	Frosted glass
Product Code	28-4073-103
Name	Elliptical spread lens
Product Code	6465-03-31
Name	150W 230V/48V DALI transformer for remote use