

Nanoperfetto-S 3000K 6.5W

54°

Design: Ivela Design Team











IP 20



Product Code	Color
752-219BVN-21	Mat white
General specifications	
Product type	Suspensions
Mounting type	Pendant
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Suspended version of Nanoperfetto spotlight, with canopy for installation in a false ceiling, equipped with a high efficiency COB LED. Professional optic devices for better visual comfort are available on demand. LED drivers should be ordered separately; the wattage of the fitting changes depending on the selected driver.
Applications	Retail , Residential , Hospitality
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle versions
Lamp description	LED 650lm 6.5W 3000K CRI90
Nominal lumens on thermal regime (Im)	650
LOR	70
Delivered lumen (lm)	425
Watt source (W)	6.5
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	12
Physical specifications	
Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive
Electrical specifications	
Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable
Optical specifications	
Light distribution	Symmetric
Emission	Direct
Light beam	54°
Weight and dimension	
Height (mm)	50

36

50

42

0.4

Width (mm)

Weight (Kg)

Recessed depth (mm)

Cutout width (mm)



Accessories



Product Code 28-4175-100
Name Satined gold baffle



Product Code 28-4200-30
Name Honeycomb
Finishing Black painted

Product Code

Name Driver 700mA dimmable on the mains

81-04027

81-04088

Product Code 81-04028

Name Driver 700mA dimmable DALI

Description For a correct installation, please consider a ceiling recessed depth of 200mm.

Product Code

Name Driver 700mA Wireless Bluetooth

