



## Nanoperfetto-S 3000K 6.5W

### 54°

Design: Ivela Design Team



IP 20



Product Code	Color
752-219BVN-16	Black

#### General specifications

Product type	Suspensions
Mounting type	Pendant
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Suspended version of Nanoperfetto spotlight, with canopy for installation in a false ceiling, equipped with a high efficiency COB LED. Professional optic devices for better visual comfort are available on demand. LED drivers should be ordered separately; the wattage of the fitting changes depending on the selected driver.
Applications	Retail , Residential , Hospitality

#### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 650lm 6.5W 3000K CRI90
Nominal lumens on thermal regime (lm)	650
LOR	70
Delivered lumen (lm)	425
Watt source (W)	6.5
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	12

#### Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

#### Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable

#### Optical specifications

Light distribution	Symmetric
Emission	Direct
Light beam	54°

#### Weight and dimension

Height (mm)	50
Width (mm)	36
Recessed depth (mm)	50
Cutout width (mm)	42
Weight (Kg)	0.4

**Accessories**

---



Product Code 28-4175-100  
Name Satined gold baffle



Product Code 28-4200-30  
Name Honeycomb  
Finishing Black painted



Product Code 81-04027  
Name Driver 700mA dimmable on the mains



Product Code 81-04028  
Name Driver 700mA dimmable DALI  
Description For a correct installation, please consider a ceiling recessed depth of 200mm.



Product Code 81-04088  
Name Driver 700mA Wireless Bluetooth