



Nanoperfetto-S 2700K 6.5W 54°

Design: Ivela Design Team



IP 20



Product Code

752-219CVN-21

Color

Mat white

General specifications

Product type	Suspensions
Mounting type	Pendant
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Suspended version of Nanoperfetto spotlight, with canopy for installation in a false ceiling, equipped with a high efficiency COB LED. Professional optic devices for better visual comfort are available on demand. LED drivers should be ordered separately; the wattage of the fitting changes depending on the selected driver.
Applications	Retail , Residential , Hospitality

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 620lm 6.5W 2700K CRI90
Nominal lumens on thermal regime (lm)	620
LOR	70
Delivered lumen (lm)	405
Watt source (W)	6.5
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	12

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	54°

Weight and dimension

Height (mm)	50
Width (mm)	36
Cutout diameter (mm)	42
Recessed depth (mm)	50
Cutout width (mm)	42
Weight (Kg)	0.4

Accessories



Product Code 28-4175-100
Name Satined gold baffle



Product Code 28-4200-30
Name Honeycomb
Finishing Black painted



Product Code 81-04027
Name Driver 700mA dimmable on the mains



Product Code 81-04028
Name Driver 700mA dimmable DALI
Description For a correct installation, please consider a ceiling recessed depth of 200mm.



Product Code 81-04088
Name Driver 700mA Wireless Bluetooth