
IVEL A.

Perfetto IP66 18W 4000K

16°

Design:





働

÷

IP 66 IK 10

Æ.



Product Code	Color
1035AZ0030	Black
General specifications	
Product type	Outdoor spotlight
Mounting location	Ground, wall or ceiling
Indoor/Outdoor light	Outdoor
Description	Exterior spotlight equipped with COB LED, suitable for outdoor applications where a powerful and ecological light is needed. It can be mounted on the wall/ceilingor in the ground through the specific spike. High protection rating IP66.
Applications	Squares , Gardens , Façades , Courtyards
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle version
Lamp description	LED 2450lm 18W 4000K CRI85
Nominal lumens on thermal regime (Im)	2450
LOR	74.1
Delivered lumen (lm)	1816
System wattage (W)	20,6
Watt source (W)	18
Color temperature (K)	4000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Physical specifications	
Body	Die-cast aluminium
Finishing	Polyester painted, with a special antioxidising pretreatment
Optic device	Mirror-metallized thermoplastic material
Gasket	Silicone
Safety glass	Grinded, tempered 3 mm, and heat resistant glass
Screws	Stainless steel
Electrical specifications	
Driver availability	Included
Driver mounting	Integrated
Dimmable	Dimmable on the mains
Voltage (V)	220/240
Frequency (Hz)	50/60
Cable gland	Nickel-plated brass M16x1,5
Supply cable	H05RN-F 3x1 mm ² , 2 mt. length
Optical specifications	
Light distribution	Symmetric
Emission	Direct

It pivots up to 90° upwards. Tiltable Light beam 16°

Ivela srl – member of Starlight Group

Aiming

IVEL ^.









Product Code	28-4130-30
Name	Asymmetric snoot
Product Code	28-04191-47
Name	Prismatic spread lens
Product Code	28-4163-30
Name	Honeycomb
Finishing	Black painted
Product Code	84108
Name	IP 68 rated cable connector
IP rating	IP 68
Product Code	28-2377-30
Name	Black thermoplastic spike
Product Code	28-4208-30
Name	Honeycomb
Finishing	Black painted
Product Code	28-04190-47
Name	Prismatic spread lens

241

72

1.4

Weight and dimension

Height (mm) Diameter (mm)

Weight (Kg)

Accessories