


Perfetto-IN 80 Tilttable 18W
2700K 21°

Design:



IP 43 IK 08



Product Code	Color
268-039CYN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Tilttable downlight, designed for COB LEDs, featuring a rearward optic for a high visual comfort. Integrated snoot in black thermoplastic material. LED drivers should be ordered separately; the wattage of the fittings changes, depending on the selected driver.
Applications	Showrooms , Retail , Residential , Hospitality

Lighting specifications**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1850lm 18W 2700K CRI90
Nominal lumens on thermal regime (lm)	1850
LOR	56
Delivered lumen (lm)	1036
Watt source (W)	18
Color temperature (K)	2700
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L90B50 50.000
Photobiological risk group	RG1

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	30° tilting.
Light beam	21° Refl.

Weight and dimension

Height (mm)	84
Diameter (mm)	82
Cutout diameter (mm)	75
Recessed depth (mm)	85
Weight (Kg)	0.4
False ceiling thickness (mm)	1-30

Accessories



Product Code 28-4163-30
Name Honeycomb
Finishing Black painted



Product Code 28-3905-47
Name Closing screen in clear thermoplastic



Product Code 28-4074-47
Name Prismatic spread lens



Product Code 28-4073-61
Name Frosted glass



Product Code 28-4073-103
Name Elliptical spread lens



Product Code 81-04011
Name Driver 500mA



Product Code 81-04002
Name Driver 500mA DALI dimmable



Product Code 81-04092
Name Driver 500mA Wireless Bluetooth