


# Microperfetto Large Base **Zoom 2700K CRI90**

Design: Ivela Design Team







IP 20









√850°



### General specifications

Product type Semi- recessed surface spotlights Mounting location Ceiling Indoor/Outdoor light Indoor Description Spotlight with base for surface application, specially developed for high-efficiency COB LEDs. It's equipped with zoom lens in PMMA and prismatic spread lens, seven

LED 1630lm 18,5W 2700K CRI90

positions adjustable and with a spotlight range from 13° to 47°, and integrated black snoot. Electronic transformer for remote use and proper dimmer to be ordered

Retail , Residential , Museums , Hospitality Applications

Color

Mat white

## Lighting specifications

Lamp description

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Nominal lumens on thermal regime (Im) 1630 LOR 67 Delivered lumen (lm) 1092 Watt source (W) 18.5 Color temperature (K) 2700 CRI CRI 90 COB LED Lamp type L80B10 50.000 Average lamp life (h)

# Physical specifications

Body Die-cast aluminium Finishing Polyester painted PMMA zoom lens Optic device Thermal dissipation Passive

### **Electrical specifications**

Driver availability Separate Driver mounting Separate Dimmable DALI dimmable

# **Optical specifications**

Light distribution Symmetric Emission Direct Light beam 13° to 47°

#### Weight and dimension

Length (mm) 145 Height (mm) 110 Diameter (mm) 61 Weight (Kg) 0.5



Accessories

 Product Code
 81-04011

 Name
 Driver 500mA

Product Code 81-04002

Name Driver 500mA DALI dimmable