


Microperfetto IP66 8,7 3000K CC DALI 21°

Design:



0,5 Kg



IP 66 IK 10



Product Code	Color
1927BYN0088	Brushed copper

General specifications

Product type	Outdoor spotlight
Mounting location	Ground
Indoor/Outdoor light	Outdoor
Description	Exterior spotlight equipped with COB LED for outdoor applications in the ground, with a spike or a bracket. It's easy to install and it guarantees, thanks to the special antioxidising treatment and the silicone gaskets, a high protection rating IP66. Bracket in AISI 304 steel, polyester painted. LED drivers should be ordered separately; the wattage of the fittings changes, depending on the selected driver.

Applications Squares , Gardens , Façades , Courtyards

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 967lm 8,7W 3000K CRI85
Nominal lumens on thermal regime (lm)	967
LOR	88
Delivered lumen (lm)	808
Watt source (W)	8.7
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium and thermoplastic material
Finishing	Polyester painted, with a special antioxidising pretreatment
Optic device	PMMA lens
Gasket	Silicone
Safety glass	Grinded, tempered and heat resistant glass
Screws	Stainless steel A4

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	DALI dimmable
Supply cable	H05RN-F 2x1 mm ² , 2 mt. length with rated cable connector

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	21°

Weight and dimension

Length (mm)	105
Diameter (mm)	53
Weight (Kg)	0.5

Accessories



Product Code 28-4499-30
Name Honeycomb



Product Code 28-4445-30
Name Asymmetric snoot



Product Code 28-2377-30
Name Black thermoplastic spike



Product Code 81-04034
Name Driver 700mA DALI IP68