



Minirooler Base 10 lights

3000K CRI90 14°+41°

Design: Ivela Design Team



IP 40



Product Code	Color
3898-019BQN-21	Mat white

General specifications

Product type	Semi- recessed surface spotlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed miniaturized linear spotlight for ceilings, featuring 10 high-efficiency LEDs of the latest generation. It grants high lighting performance, low glare levels and homogeneous light distribution. LED drivers should be ordered separately; the wattage of the fittings changes, depending on the selected driver.
Applications	Offices , Residential , Shops , Showrooms , Hospitality

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1100lm 10,4W 3000K CRI90
Nominal lumens on thermal regime (lm)	1100
LOR	69
Delivered lumen (lm)	759
Watt source (W)	10.4
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	10 PMMA microlenses
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	14°+41° Long.

Weight and dimension

Length (mm)	140
Width (mm)	23

Accessories

Product Code	81-04003
Name	Driver 350mA DALI - 1/10V - Push dimmable
Description	Max 1 fittings





Product Code	81-04010
Name	Driver 350mA dimmable on the mains
Description	Max 1 fitting