


Perfetto-IN 40 with lens
3000K CRI90 14°

Design:



IP 43 IK 07

**Product Code**

254-219BZN-16

Color

Black

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Fixed downlight with no replaceable lens and prismatic spread lens, equipped with LED of latest generation. Inner snoot in black thermoplastic material. LED drivers should be ordered separately; the wattage of the fitting changes depending on the selected driver.
Applications	Showrooms , Residential , Hospitality , Commercial areas

Lighting specifications**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 200lm 3W 3000K CRI90
Nominal lumens on thermal regime (lm)	200
LOR	85
Delivered lumen (lm)	170
Watt source (W)	3
Color temperature (K)	3000
CRI	CRI 90
Lamp type	High Power LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	9

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate

Optical specifications

Light distribution	Symmetric
Emission	Accent light
Aiming	Fixed
Light beam	14° Lens

Weight and dimension

Height (mm)	45
Diameter (mm)	41
Cutout diameter (mm)	36
Recessed depth (mm)	45
Weight (Kg)	0.1
False ceiling thickness (mm)	1-30

Accessories



Product Code	28-4105-100
Name	Satined gold baffle



Product Code	81-02531
Name	Driver 700mA Constant current
Description	Max 3 fittings