
IVEL ^.

35 Linear master element 1000mm 2700K

Design: Ivela Design Team







IP 20

| 457-230109C-0462 | White + opal diffuser |
|--|--|
| | |
| General specifications | |
| Product type | Linear lights |
| Mounting type | Suspended linear system |
| Mounting location | Ceiling |
| Indoor/Outdoor light | Indoor |
| Description | The Master element of 35 Linear is made of an aluminium linear element with o polycarbonate diffusers. It is supplied with one straight joint for electrical continuity and with one supply ca of L=3 mt. Double switch: 120° (up) - 240° (down). Maximum load capacity: 200W. Transformers should be ordered separately. |
| Product notes | |
| Applications | Offices , Museums , Art-galleries , Restaurants , Hospitality , Showrooms , Retail |
| Lighting specifications | i Stated L.O.R. and delivered lumens values are related to standard beam angle version |
| Lamp description | LED 1050+2100lm 10+20W 2700K CRI90 |
| Nominal lumens on thermal regime (Im) | 1050+2100 |
| Delivered lumen (lm) | 586+1172 |
| Watt source (W) | 10+20 |
| Color temperature (K) | 2700 |
| CRI | CRI 90 |
| Photobiological risk group | RG1 |
| Diffuser | Opal polycarbonate |
| Unified Glare Rating (U.G.R. <) | 15 |
| Physical specifications | |
| Body | Aluminium |
| Electrical specifications | |
| 48VDC electronic transformer availability | Not included |
| 48VDC electronic transformer mounting | Separate |
| Dimmable | PWM |
| Voltage (V) | 48 |
| Optical specifications | |
| Emission | Double switch (120° + 240°) |
| Weight and dimension | |
| Length (mm) | 1000 |
| Diameter (mm) | 35 |
| Accessories | |
| | 46.11 |
| Product Code | 46-11 |
| Name | Smoked diffuser (500mm length) |

IVEL ^.



Documento generato il14 May 2024 Ore 12:11:44 Pagina 2 di2 www.ivela.it