



## 35 Linear continuous element 2000mm 2700K

Design: Ivela Design Team



IP 20

| Product Code     | Color                          |
|------------------|--------------------------------|
| 458-230209C-1262 | Anodized black + opal diffuser |

### General specifications

|                      |   |
|----------------------|---|
| Product type         | Linear lights   |
| Mounting type        | Suspended linear system   |
| Mounting location    | Ceiling   |
| Indoor/Outdoor light | Indoor  |
| Description          | The Continuous element of 35 Linear is made of an aluminium linear element with opal polycarbonate diffusers. It is supplied with one straight joint for electrical continuity. Double switch: 120° (up) - 240° (down). Maximum load capacity: 200W. Master linear element and transformers should be ordered separately. |
| Applications         | Showrooms , Retail , Offices , Restaurants , Hospitality , Museums , Art-galleries  |

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Lamp description                      | LED 2100+4200lm 20+40W 2700K CRI90 |
| Nominal lumens on thermal regime (lm) | 2100+4200lm                        |
| Delivered lumen (lm)                  | 1172+2344                          |
| Watt source (W)                       | 20+40                              |
| Color temperature (K)                 | 2700                               |
| CRI                                   | CRI 90                             |
| Photobiological risk group            | RG1                                |
| Diffuser                              | Opal polycarbonate                 |
| Unified Glare Rating (U.G.R. <)       | 15                                 |

### Physical specifications

|      |           |
|------|-----------|
| Body | Aluminium |
|------|-----------|

### Electrical specifications

|   |              |
|---|--------------|
| 48VDC electronic transformer availability | Not included |
| 48VDC electronic transformer mounting     | Separate     |
| Dimmable                                  | PWM          |
| Voltage (V)                               | 48           |

### Optical specifications

|          |                             |
|----------|-----------------------------|
| Emission | Double switch (120° + 240°) |
|----------|-----------------------------|

### Weight and dimension

|               |      |
|---------------|------|
| Length (mm)   | 2000 |
| Diameter (mm) | 35   |

### Accessories

|              |                                |
|--------------|--------------------------------|
| Product Code | 46-11                          |
| Name         | Smoked diffuser (500mm length) |

|              |                                 |
|--------------|---------------------------------|
| Product Code | 46-05-00                        |
| Name         | Suspension kit (3 mt - 1 piece) |





Product Code 46-13-16  
Name Kit for wall/ceiling mounting (3 pieces)



Product Code 46-02-16  
Name Flexible joint



Product Code 46-01-16  
Name L joint



Product Code 46-18-16  
Name Black L joint with power cable



Product Code 46-12-16  
Name Canopy



Product Code 81-90089  
Name Bluetooth Casambi dimmer 48V 4 channels



Product Code 81-90123  
Name PWM dimmer



Product Code 81-09000  
Name 100W 230V/48V PWM transformer for remote use



Product Code 81-09001  
Name 200W 230V/48V PWM transformer for remote use



Product Code 81-04085  
Name Wireless Bluetooth dimmable transformer